

Amendments to the Claims: This listing of claims will replace all prior versions, and listings, of claims in the application

Listing of Claims:

1. (Currently Amended) A system for mounting a computer component, said system comprising:

at least one rail, said rail having first and second mounting portions, said first mounting portion defining a recess and said second mounting portion having at least one detent; and

first and second supports, said first support having an extension extending into said recess of said first mounting portion of said rail and allowing sliding of said first mounting portion of said rail relative to said first support, said second support defining at least one aperture receiving said detent of said second mounting portion of said rail and limiting sliding of said second mounting portion of said rail relative to said second support[[]].

wherein the recess is substantially parallel to the rail and the rail is substantially orthogonal to the first support, so that the rail slides substantially orthogonally to the first support.

2. (Original) The system of claim 1, wherein the second mounting portion has a plurality of detents.

3. (Original) The system of claim 1, wherein the recess extends adjacent a surface of the rail and the detent extends from said surface.

4. (Currently Amended) The system of claim 2, wherein the plurality of detents extend from ~~said~~ a surface of the rail.

5. Canceled

6. (Original) The system of claim 1, having a plurality of detents on the second mounting portion of the rail and a corresponding plurality of apertures defined in said second support.

7. (Currently Amended) The system of claim 1, wherein the at least one aperture comprises a first portion and a second portion, the first portion being sized to receive the detent along an axis of the detent and the second portion being sized preventing removal of the detent along the axis of the detent.

8. (Currently Amended) A support assembly for a computer component, comprising:

a rail;

a support adjacent the rail;

a detent extending from said rail or said support and engaged

with an aperture defined in ~~the other~~ one of said rail or said support;

an extension coupled to the support, the extension having a portion moveable with respect to the support between a first position preventing sliding of the rail with respect to the support and a second position permitting sliding of the rail with respect to the support.

9. (Original) The support assembly of claim 8, wherein the rail has at least one recess extending along a surface of the rail.

10. (Original) The support assembly of claim 8, wherein the rail has at least one detent formed on the surface of the rail.

11. (Currently Amended) The support assembly of claim 8, wherein the support has at least one aperture in a portion of the support receiving the detent.

12. (Currently Amended) The support assembly of claim ~~8~~ 9, wherein the support has at least one other extension extending into the at least one recess of said rail.

13. (Currently Amended) The system of claim 89, wherein a width of the extension is greater than a width of the at least one recess.

14. (Currently Amended) The system of claim 89, wherein the at least one recess is oriented along a plane and the extension is positioned in the plane of the at least one recess when the extension is in the first position.

15. (Original) The system of claim 14, wherein the extension is away from the plane of the recess when the extension is in the second position.

16. (Original) The system of claim 15, further comprising a plurality of detents extending from said rail or said support engaged with respective ones of apertures defined in the other of said rail or said support.

17. (Currently Amended) A method of mounting a rail in a frame of a computer system, the method comprising the steps of:

positioning the rail adjacent first and second supports;

engaging a recess in a first mounting portion of the rail with ~~an~~ a first extension on the first support, thereby permitting sliding movement of the rail with respect to the first support;

engaging a detent on a second mounting portion of the rail with an aperture formed in the second support, thereby limiting the sliding movement of the rail with respect to the second support; and

moving a second extension coupled to the first or second support to a position substantially preventing sliding movement of the rail.

18. (Original) The method of claim 17, further comprising the step of sliding the rail between first and second positions with respect to the first and second supports.

19. (Original) The method of claim 17, wherein the step of engaging the detent comprises the steps of inserting the detent into a first portion of the aperture and sliding the detent from the first portion into a second portion of the aperture.
20. Canceled.